

100 SERIES GLOSS HOUSE PAINT

Exterior Oil-Based

DESCRIPTION:	A superior, long wearing house paint that flows smoothly, applies easily and dries to a hard, durable film that is resistant to cracking, peeling, dirt and weather streaking.
USES:	This non-chalking product may be used on exterior wood and metal surfaces including shutters, trim, doors, window sashes and siding.
VEHICLE TYPE:	Long oil alkyd
SHEEN:	Gloss
SPREAD RATE:	350-450 square feet per gallon on smooth surfaces.
DRYING TIME @ 75°F:	To touch: 8 hours To recoat: 24 hours
THINNER:	Do not thin this product.
APPLICATION:	Stir thoroughly before using. Application may be by brush, roller, or spray. Most types of spray equipment are acceptable for spray application. Always wear a respirator when spraying and protect yourself and your surroundings from spray mist. Wet spray mist will drift thousands of feet.
LIMITATIONS:	Do not apply when temperature is below 50°F or might drop below 50°F within 4 hours. Do not paint in late afternoon or when there is danger of rain or moisture condensing on wet film. Do not use in high temperature service. (See notes on back).
COLORS:	White and tint bases. For custom tint colors, see "Color Is" Color System.
CLEAN UP:	Clean up with mineral spirits while paint is still wet. This product is difficult to remove when dry.
AVAILABILITY:	Gallon and quart containers
% SOLIDS BY VOLUME:	59.0% ± 2% (111 White)
% SOLIDS BY WEIGHT:	74.0% ± 2% (111 White)
V. O. C.:	331 grams/liter or 2.77 lbs/gallon (bases vary slightly)

SURFACE PREPARATION - GENERAL PRACTICE

For proper adhesion, surface should be clean, dry, non-greasy and properly primed. Remove mildew, dirt, surface contamination, loose and scaling paint, efflorescence, loose surface particles, water soluble stains and rust before painting. Allow all recommended primers to thoroughly dry before applying one or two coats of finish paint.

In the recommendations below, certain steps must be taken to prepare surfaces for painting independent of the substrate. Therefore, the following steps must be taken to assure a quality paint job:

REMOVAL OF MILDEW -- Remove mildew with a commercially prepared solution or use: 5 oz. (2/3 cup) Trisodium Phosphate (TSP), 3 oz. (1/3 cup) detergent, 1 qt. household bleach and 3 qts. warm water which will make a little over one gallon.

SEALING KNOTS AND STAINS WHICH MAY BLEED THROUGH PAINT FILM -- Spot prime knots or stained area with 3077 ProMax Alkyd Uniblox Universal Primer and let dry. Then prime entire surface with appropriate primer. Woods subject to tannin bleedthrough (cedar, redwood, etc.) should be primed entirely with 3077. If stains show through the primer coat, these areas should be primed again before finishing.

REMOVAL OF CONTAMINANTS -- All contaminants, such as grease, oil, dirt, etc., which would interfere with either the adhesion or aesthetic appeal of the finish should be removed.

SURFACE PREPARATION AND PRIMING

WOOD -- Repair construction defects and countersink all nails. Prime new wood with 19 House Paint Primer. Allow primer to thoroughly dry (at least 48 hours at 75°F). Fill nail holes and apply one or two finish coats of paint. For repainting wood surfaces, remove loose paint and sand smooth the remaining edges. Spot prime bare areas with 19 House Paint Primer before applying finish coat(s).

FERROUS METAL -- Remove all loose rust, mill scale and dirt with abrasive cleaning. Prime bare areas with 59 Red Oxide Primer. Allow primer to thoroughly dry (at least 48 hours at 75°F) before applying topcoat(s).

NOTE -- During the early Spring and Fall periods of the year, daytime temperatures may seem warm. However, nighttime temperatures may be much colder than expected which will cause dry time of paint to be lengthened significantly. This leaves the film open to moisture attack for long periods. Frequently, during these times of year, condensation will form on freshly painted surfaces in the form of dew. This will cause patchy areas where the dew will etch the paint surface. When viewed, this appears as a splotchy color change on the painted surface.

WARNING! If you scrape, sand or remove old paint, you may release lead dust. **LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE.** Wear a NIOSH-approved respirator to control lead exposure. Carefully clean up with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hotline at 1-800-424-LEAD or log on to www.epa.gov/lead.

PRECAUTIONS! COMBUSTIBLE! Keep away from heat and flame.
Avoid prolonged contact with skin and breathing of vapor or spray mist.
USE ONLY WITH ADEQUATE VENTILATION.

CAUTION!

Do not take internally.
Close container after each use.

**CONTAINS PETROLEUM
DISTILLATE!**

**KEEP OUT OF REACH
OF CHILDREN!**

LIMITED WARRANTY

DAVIS-FROST, INC. warrants this product will perform satisfactorily when applied over properly prepared surfaces in accordance with label directions; product failure due to deterioration of the underlying surface or failure of previous products is excluded. If the product fails to perform to your satisfaction, return any unused portion to the store with proof-of-purchase and you will receive, as your sole remedy under this warranty, your choice of additional product of equal value or a full refund. THIS WARRANTY EXCLUDES LABOR OR THE COST OF LABOR FOR THE APPLICATION OF ANY PRODUCT AND EXCLUDES ANY INCIDENTAL OR CONSEQUENTIAL DAMAGES. Some states do not allow the exclusion or limitation of incidental or consequential damages, so the above limitations or exclusions may not apply to you. This warranty gives you specific rights, and you may also have other rights which vary from state to state.