

1051 "ECO-GREEN" PREMIUM BLOCK FILLER

Interior & Exterior Latex

DESCRIPTION:	A heavy bodied latex coating designed to fill the holes and pores of lightweight concrete and cinder block, and other rough masonry surfaces. Cleans up easily with soap and water.
USES:	Use on new, unpainted surfaces to produce a uniformly filled surface to which other latex, acrylic, oil, alkyd, epoxy paints and enamels may be applied. While this product may be used as a finish coat on interior surfaces, it must be topcoated when used on exterior surfaces.
VEHICLE TYPE:	Vinyl Acrylic
SHEEN:	Flat
SPREAD RATE:	50-100 square feet/gallon. Coverage depends on porosity of surface.
DRYING TIME @ 75°F:	To touch: 1 hr. To recoat: 8 hrs.
THINNER:	If necessary, this product may be thinned slightly with water. However, it is important to note that over-thinning will reduce the filling capacity and general performance of this material. May also be thinned with an appropriate latex paint.
APPLICATION:	See instructions on reverse side.
LIMITATIONS:	Although this block filler makes it more difficult for water and moisture to penetrate the block, it is not a waterproof coating and should not be used in lieu of a true waterproofing system. Do not use in areas where moisture is likely to enter surface behind filler particularly when topcoating with a non-breather paint such as an alkyd, epoxy, or vinyl. Not recommended for continually moist areas. Do not apply when temperature is below 50°F, or when there is likelihood of rain or moisture condensing on the uncured film.
COLOR:	White
CLEAN UP:	Clean up with soap and warm water while paint is still wet. Dry paint is almost impossible to remove.
AVAILABILITY:	5-gallon containers
% SOLIDS BY VOLUME:	48.0% ± 2%
% SOLIDS BY WEIGHT:	69.0% ± 2%
V. O. C.:	Less than 50 grams/liter

081616

DAVIS-FROST, INC.

3416 Candler's Mountain Road ▪ Lynchburg, VA 24502 ▪ Ph (434)846-5277 ▪ Fx (434)846-0635

SURFACE PREPARATION AND APPLICATION

For proper adhesion, clean surface thoroughly to remove dirt, grease, oil, curing compounds, efflorescence, loose surface particles, and other surface contaminants. For optimum results, dampen surface with clean, fresh water prior to application.

Stir thoroughly before using. Application may be by trowel, squeegee, short bristle brush, roller or spray. Proper application should force the block filler well into the surface being filled. Apply liberally to avoid pinholes in the finished filled areas. When dry, sand lightly prior to topcoating.

When spraying, optimum results are obtained by application with an airless sprayer and then backrolling to press the filler into the pits and voids. Always wear a respirator when spraying and protect yourself and your surroundings from spray mist.

When topcoating with a latex product, allow the filler to thoroughly dry (at least 8 hours at 70°F) before topcoating. If the topcoat is not latex, allow this filler to cure 24 hours prior to topcoating. At that time, test to be sure the surface is thoroughly dry.

WARNING! If you scrape, sand or remove old paint, you may release lead dust. **LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE.** Wear a NIOSH-approved respirator to control lead exposure. Carefully clean up with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hotline at 1-800-424-LEAD or log on to www.epa.gov/lead.

CAUTION!

Do not take internally.
Close container after each use.

PROTECT FROM FREEZING!

**KEEP OUT OF REACH
OF CHILDREN!**

LIMITED WARRANTY

DAVIS-FROST, INC. warrants this product will perform satisfactorily when applied over properly prepared surfaces in accordance with label directions; product failure due to deterioration of the underlying surface or failure of previous products is excluded. If the product fails to perform to your satisfaction, return any unused portion to the store with proof-of-purchase and you will receive, as your sole remedy under this warranty, your choice of additional product of equal value or a full refund. THIS WARRANTY EXCLUDES LABOR OR THE COST OF LABOR FOR THE APPLICATION OF ANY PRODUCT AND EXCLUDES ANY INCIDENTAL OR CONSEQUENTIAL DAMAGES. Some states do not allow the exclusion or limitation of incidental or consequential damages, so the above limitations or exclusions may not apply to you. This warranty gives you specific rights, and you may also have other rights which vary from state to state.