

1200 SERIES SATIN SHEEN DTM

All Purpose Interior/Exterior 100% Acrylic Enamel

- DESCRIPTION:** The 1200 Line is a waterborne satin sheen all purpose enamel for both interior and exterior use. It is designed as a direct-to-metal, low VOC product that is both durable and corrosion resistant. Adheres to oil-based finishes without priming. Ideal for moderate to heavy traffic areas in residential, commercial and institutional settings.
- USES:** Excellent for industrial usage on machinery, piping, structural steel, galvanized metal, aluminum, and properly primed wood. Also ideal for institutional applications on walls, corridors and trim. Household uses include furniture, wood trim, drywall, masonry, and metal. May be applied directly over oil based finishes with proper preparation (see reverse – Previously Painted Surfaces).
- VEHICLE TYPE:** 100% Acrylic
- SHEEN:** Satin: 25-35% @ 60°
- SPREAD RATE:** 350-450 square feet per gallon
- DRYING TIME @ 77°F:** To touch: 1 hour To recoat: 4 hours Full cure: 14-30 days
- At approximately 77° and 50% relative humidity, this product dries at the above rate. Drying times listed may vary depending on temperature, humidity, color and air movement.
- THINNER:** If necessary, use water 4 oz. per gallon.
- APPLICATION:** Stir thoroughly. Application may be by brush, roller or spray.
- LIMITATIONS:** Avoid use in direct sunlight on a hot day. Do not apply when temperature is below 50°F. Do not use in high temperature (160°F) service. For improved open time, mix with latex paint conditioner such as Floetrol. This product is not recommended for exterior use on wood substrates which are subject to expansion and contraction due to moisture and weather.
- COLOR:** White, Satin Bronze and tint bases
- CLEAN UP:** Clean up with soap and warm water while paint is still wet. Dry paint is almost impossible to remove.
- AVAILABILITY:** White and White Base in 5-gallon, gallon and quart containers. Satin Bronze in 5-gallon and gallon containers. All other tint bases in gallons and quarts.
- % SOLIDS BY VOLUME:** 38.0% ± 2% (bases vary slightly)
- % SOLIDS BY WEIGHT:** 51.0% ± 2% (bases vary slightly)
- V. O. C.:** 146 grams/liter, 1.22 lbs/gallon (bases vary slightly)

SURFACE PREPARATION

For best adhesion, surfaces should be clean, dry, and non-greasy. Remove all mildew, dirt, grease, loose rust and loose, scaling paint before painting. Allow all recommended primers to thoroughly dry before applying one or two coats of finish paint.

PREVIOUSLY PAINTED SURFACES: May be applied over surfaces previously painted with oil/alkyd paints or acrylic paints. Oil/Alkyd paints must be thoroughly cured before repainting. Remove loose and flaking paint. Spot prime bare areas with appropriate primer and allow complete drying before finishing. No primer is required if in sound condition and of uniform porosity. Remove dirt, grease or peeling paint from surface. Clean by washing with detergent and water. Rinse thoroughly and allow complete drying. Dull glossy surfaces by sanding with fine sandpaper.

FERROUS METALS: Remove all surface rust. Remove grease and oil with appropriate solvent. Prime exposed areas with Davis 1959 Water-Tuff® WB Red Oxide Primer or 1912 Water-Tuff® Gray DTM Primer.

GALVANIZED METAL: Surface should be exterior weathered for six months and be clean, dry and free from dirt, grease, mildew and other surface contaminants. Rusty galvanized metals should be cleaned and primed as ferrous metals.

ALUMINUM: Remove all grease, dirt, oxide and foreign matter with appropriate solvent. No primer is necessary for new aluminum surfaces.

NEW DRYWALL – Repair construction defects and fill openings with spackling. Prime with 5062 ProMax Latex Drywall Primer, 167 Latex Primer Sealer or 5088 ProMax “Eco-Green” Acrylic Uniblox Bonding Primer. Allow primer to thoroughly dry (at least 2 hours at 75°F). Scuff sand with fine sandpaper to remove raised nap. Apply one or two coats of finish paint as necessary.

PLASTER AND MASONRY: Apply only to firm, fully cured and dust free plaster or masonry surfaces. Fill construction defects with spackling. When dry inspect for “dry spots” in plaster. If necessary, spot prime these areas.

WARNING! If you scrape, sand or remove old paint, you may release lead dust. **LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE.** Wear a NIOSH-approved respirator to control lead exposure. Carefully clean up with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hotline at 1-800-424-LEAD or log on to www.epa.gov/lead.

CAUTION!

Do not take internally.
Close container after each use.

PROTECT FROM FREEZING!

**KEEP OUT OF REACH
OF CHILDREN!**

LIMITED WARRANTY

DAVIS-FROST, INC. warrants this product will perform satisfactorily when applied over properly prepared surfaces in accordance with label directions; product failure due to deterioration of the underlying surface or failure of previous products is excluded. If the product fails to perform to your satisfaction, return any unused portion to the store with proof-of-purchase and you will receive, as your sole remedy under this warranty, your choice of additional product of equal value or a full refund. THIS WARRANTY EXCLUDES LABOR OR THE COST OF LABOR FOR THE APPLICATION OF ANY PRODUCT AND EXCLUDES ANY INCIDENTAL OR CONSEQUENTIAL DAMAGES. Some states do not allow the exclusion or limitation of incidental or consequential damages, so the above limitations or exclusions may not apply to you. This warranty gives you specific rights, and you may also have other rights which vary from state to state.