

1301 CLEAR DECK & SIDING FINISH

Exterior Oil-Based

DESCRIPTION:	A high quality oil-based clear finish waterproofer for use on properly prepared wood surfaces. This product penetrates the wood for maximum protection against harsh weather, water, and UV rays. Resists cracking, peeling, and blistering.
USES:	Excellent for use on decks, siding, and shingles. Also provides protection on rough sawn surfaces, as well as premium grade lumbers such as cedar and redwood. May be used on pressure treated wood.
VEHICLE TYPE:	Phenolic Alkyd
SHEEN:	Low
SPREAD RATE:	200 to 400 square feet per gallon depending on surface texture and porosity
DRYING TIME @ 75°F:	To touch: 6 hours To recoat: 12 hours
THINNER:	It is not necessary to thin this product. Clean up with mineral spirits.
APPLICATION:	Stir thoroughly before and occasionally while using. Apply with brush, roller or sprayer. If rolled or sprayed, always back brush immediately with a high quality china bristle brush for best penetration. One coat is recommended for vertical surfaces, i.e. siding, shingles, shakes, etc. For best protection, two coats are recommended for deck areas.
LIMITATIONS:	Do not apply when temperature is below 50°F or might drop below 50°F within 4 hours. Do not paint in late afternoon or when there is danger of rain or moisture condensing on wet film. Do not use in high temperature (160° F) service. Should not be applied to previously painted or sealed surfaces, metal or masonry substrates. For exterior use only.
COLORS:	Clear, honey tint
CLEAN UP:	Clean up with mineral spirits while stain is still wet. This product is almost impossible to remove when dry.
AVAILABILITY:	Gallon containers
% SOLIDS BY VOLUME:	31.0% ± 2%
% SOLIDS BY WEIGHT:	38.0% ± 2%
V. O. C.:	550 grams/liter or 4.60 lbs/liter

SURFACE PREPARATION

It is important for proper application and absorption of this product that the surface be clean from all dirt, mildew, algae, loose wood fibers and other contaminants. The surface must be sound and absolutely dry. Typically, exposure to dry weather for 72 hours is sufficient.

NEW WOOD – New wood that is unseasoned or appears shiny (mill glaze) should be weathered at least three months. **Wood should be coated prior to graying or checking as it can age too long to accept coating.** An alternative to this waiting period is to sand to allow for proper penetration, and then pressure wash.

New pressure treated wood should be scrubbed with a trisodium phosphate (TSP) solution and rinsed with a pressure washer. Pressure washed surfaces should be dried for 72 hours before coating. Grade stamps or pencil marks should be removed by sanding.

PREVIOUSLY STAINED WOOD – Must be sanded and scrubbed with a detergent solution and stiff bristle brush or pressure washed. Pressure washing is the most effective surface preparation method. In this way loose surface wood fibers, dirt, mildew, chalk and other contaminants are easily removed. All surfaces must be structurally sound and completely dry before coating.

MILDEW – All mildew and algae must be removed before finishing. Remove mildew with a commercially prepared solution or use: 5 oz. (2/3 cup) Trisodium Phosphate (TSP), 3 oz. (1/3 cup) detergent, 1 qt. household bleach and 3 qts. warm water which will make a little over one gallon. It is recommended that this solution be applied with a garden sprayer and to scrub the surface with a stiff bristle brush. Once mildew is removed, rinse surface thoroughly and allow it to dry before staining.

WARNING! If you scrape, sand or remove old paint, you may release lead dust. **LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE.** Wear a NIOSH-approved respirator to control lead exposure. Carefully clean up with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hotline at 1-800-424-LEAD or log on to www.epa.gov/lead.

PRECAUTIONS! COMBUSTIBLE! Keep away from heat and flame.
Avoid prolonged contact with skin and breathing of vapor or spray mist.
USE ONLY WITH ADEQUATE VENTILATION.

CAUTION!

Do not take internally.
Close container after each use.

**CONTAINS PETROLEUM
DISTILLATE!**

**KEEP OUT OF REACH
OF CHILDREN!**

LIMITED WARRANTY

DAVIS-FROST, INC. warrants this product will perform satisfactorily when applied over properly prepared surfaces in accordance with label directions; product failure due to deterioration of the underlying surface or failure of previous products is excluded. If the product fails to perform to your satisfaction, return any unused portion to the store with proof-of-purchase and you will receive, as your sole remedy under this warranty, your choice of additional product of equal value or a full refund. THIS WARRANTY EXCLUDES LABOR OR THE COST OF LABOR FOR THE APPLICATION OF ANY PRODUCT AND EXCLUDES ANY INCIDENTAL OR CONSEQUENTIAL DAMAGES. Some states do not allow the exclusion or limitation of incidental or consequential damages, so the above limitations or exclusions may not apply to you. This warranty gives you specific rights, and you may also have other rights which vary from state to state.