

167 "ECO-GREEN" ENAMEL UNDERCOATER & PRIMER SEALER

Interior Latex

DESCRIPTION: An interior enamel undercoater and primer/sealer for priming walls, ceilings,

woodwork, and plaster. This product binds down nap on drywall better than solvent-thinned sealers. It is easy to apply, dries quickly and cleans up with

soap and water.

USES: Use as an interior primer/sealer under all types of latex and alkyd paints and

enamels. May be used on new drywall, plaster, masonry, and wood.

VEHICLE TYPE: Vinyl Acrylic

SHEEN: Low

SPREAD RATE: 350-450 square feet per gallon

DRYING TIME @ 75°F: To touch: 1 hr. To recoat: 2 hrs.

THINNER: If necessary, add up to 1/2 pint of water per gallon.

APPLICATION: Stir thoroughly before using. Application may be by brush, roller or spray. Most

types of spray equipment are acceptable for spray application. Always wear a respirator when spraying and protect yourself and your surroundings from spray

mist.

LIMITATIONS: Do not apply when temperature is below 50°F. Do not use in high temperature

(160°F) service. For interior use only.

COLOR: White, but may be lightly tinted.

CLEAN UP: Clean up with soap and warm water while paint is still wet. Dry paint is almost

impossible to remove.

AVAILABILITY: 5-gallon, gallon, and quart containers

% SOLIDS BY VOLUME: $36.0\% \pm 2\%$

% SOLIDS BY WEIGHT: 55.0% ± 2%

V. O. C.: 46 grams/liter or .38 lbs./gal.



SURFACE PREPARATION - GENERAL PRACTICE

For best adhesion, surfaces should be clean, dry, and non-greasy. Remove all mildew, dirt and grease before priming. Allow this primer to thoroughly dry before applying one or two coats of finish paint.

<u>NEW DRYWALL:</u> Fill construction defects with spackling. Prime with this product. Allow to thoroughly dry. Scuff sand with fine sandpaper to remove raised nap before applying finish coat(s).

<u>PLASTER AND MASONRY:</u> Apply only to firm, fully cured and dust free plaster or masonry surfaces. Fill construction defects with spackling. Prime with this product.

<u>NEW WOOD:</u> Repair construction defects and countersink all nails. Prime with this product. When dry, scuff sand with fine sandpaper to remove raised grain. Fill all nail holes, knots, corners, etc., prior to topcoating.

<u>SEALING KNOTS AND STAINS WHICH MAY BLEED THROUGH PAINT FILM:</u> Spot prime knots or stained areas with 3077 ProMax Alkyd Uniblox Universal Primer or 5088 ProMax "Eco-Green" Acrylic Uniblox Bonding Primer and let dry. Then prime entire surface with appropriate primer. Woods subject to tannin bleedthrough (cedar, redwood, etc.) should be primed entirely with 3077 or 5088. If stains show through the primer coat, these areas should be primed again before finishing.

WARNING! If you scrape, sand or remove old paint, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH-approved respirator to control lead exposure. Carefully clean up with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hotline at 1-800-424-LEAD or log on to www.epa.gov/lead.

CAUTION!

Do not take internally. Close container after each use.

PROTECT FROM FREEZING!

KEEP OUT OF REACH
OF CHILDREN!

LIMITED WARRANTY

DAVIS-FROST, INC. warrants this product will perform satisfactorily when applied over properly prepared surfaces in accordance with label directions; product failure due to deterioration of the underlying surface or failure of previous products is excluded. If the product fails to perform to your satisfaction, return any unused portion to the store with proof-of-purchase and you will receive, as your sole remedy under this warranty, your choice of additional product of equal value or a full refund. THIS WARRANTY EXCLUDES LABOR OR THE COST OF LABOR FOR THE APPLICATION OF ANY PRODUCT AND EXCLUDES ANY INCIDENTAL OR CONSEQUENTIAL DAMAGES. Some states do not allow the exclusion or limitation of incidental or consequential damages, so the above limitations or exclusions may not apply to you. This warranty gives you specific rights, and you may also have other rights which vary from state to state.