

1800 SERIES WEATHERHIDE SEMI-GLOSS HOUSE & TRIM PAINT

100% Acrylic Exterior with Microban® Antimicrobial Product Protection

DESCRIPTION: A premium quality, acrylic semi-gloss house paint. The 100% acrylic formula provides excellent durability, adhesion, and mildew resistance on the paint film.

USES: Use on properly prepared exterior surfaces of wood, brick, masonry, stucco, vinyl, concrete block, aged aluminum, primed and aged galvanized metal. This durable semi-gloss finish is excellent for exterior trim and doors made of wood, fiberglass, steel or aluminum, aluminum siding, and primed hardboard siding.



This product contains built-in Microban® antimicrobial protection. Microban protection is a broad-spectrum antimicrobial which has bacteriostatic and fungistatic properties. Microban protection inhibits the growth of odor and stain causing bacteria, mold and mildew on the dried paint film. Microban additives are registered and in compliance with the EPA for use in paint and engineered to last the useful life of the paint film by guarding against discoloration and degradation caused by microorganisms. The Microban additive used does not contain triclosan. This product does not protect users or others against food-borne or disease-causing bacteria, and does not take the place of normal cleaning and disinfecting procedures. Built-in Microban protection is introduced into the molecular structure of the paint film and is designed to neither wear out nor wash away.

Microban® is a registered trademark of Microban Products Company. For more information, visit www.microban.com.

VEHICLE TYPE: 100% Acrylic

SHEEN: Semi-Gloss: 40 – 55 @ 60°

SPREAD RATE: 350-450 square feet per gallon. Coverage figures do not include loss due to surface irregularities and porosity of material or loss due to application method or mixing.

DRYING TIMES @ 75°F: To touch: 1 hour To recoat: 4 hours To full cure: 30 days
Drying times listed may vary depending on temperature, humidity, film build, color and air movement.

THINNER: If necessary, thin sparingly with small amounts of water.

APPLICATION: Stir thoroughly. Application may be by brush, roller or spray. Always wear a respirator when spraying. For best results and protection from the elements, one primer coat and two topcoats on all previously unpainted surfaces is recommended. Cleans up easily with soap and water while paint is still wet.

LIMITATIONS: Avoid use in direct sunlight on a hot day. Do not apply when temperature is below 50°F, this may affect color and sheen. Do not paint in late afternoon or where there is danger of rain or moisture condensing on the wet film. Do not use in high temperature (160°F) service. For exterior use only.

COLORS: White and tint bases. Five stock colors, see Weatherhide Ready Mix color card. For custom tint colors, see “Color Is” Color System.

AVAILABILITY: White and White Base in 5-gallon, gallon and quart containers. Stock colors and other tint bases in gallons and quarts.

% SOLIDS BY VOLUME: 38.0% ± 2% (bases and stock colors may vary)

% SOLIDS BY WEIGHT: 51.0% ± 2% (bases and stock colors may vary)

V. O. C.: 140 grams/liter or 1.17 lbs/gallon (bases and stock colors may vary)

**Product data calculations based on 1801.*

Product Data (pg. 2)

1800 Series



WARRANTY: Weatherhide 1800 Series with Microban® Antimicrobial Protection is guaranteed for five (5) years from the date of application to provide protection of the dried paint film from mold and mildew, when two coats are applied according to the label directions. All existing mold and mildew must be completely removed before painting. This warranty does not cover mold or mildew growth on dirt, dust, or other organic matter on the paint film. Painted surfaces should be cleaned regularly. All warranties and guarantees are limited to replacement or refunded value of product actually used in affected area. Claims must be supported by proof of purchase. This warranty does not cover labor or cost of labor for the application of any paint.

SURFACE PREPARATION – GENERAL PRACTICE

For proper adhesion, surface should be clean, dry, non-greasy and properly primed. Remove mildew, dirt, surface contamination, loose and scaling paint, efflorescence, loose surface particles, water soluble stains and rust before painting. Allow all recommended primers to dry thoroughly before applying one or two coats of finish paint.

In the recommendations below, certain steps must be taken to prepare surfaces for painting independent of the substrate. Therefore, the following steps must be taken to assure a quality paint job:

REMOVAL OF MILDEW – Remove mildew with a commercially prepared solution or use: 5 oz. (2/3 cup) Trisodium Phosphate (TSP), 3 oz. (1/3 cup) detergent, 1 qt. household bleach and 3 qts. warm water which will make a little over one gallon. Rinse thoroughly with clean water and allow to dry.

SEALING KNOTS AND STAINS WHICH MAY BLEED THROUGH PAINT FILM – Spot prime knots or stained areas with 3077 ProMax Alkyd Uniblox Universal Primer or 5088 ProMax “Eco-Green” Acrylic Uniblox Bonding Primer and let dry. Then prime entire surface with appropriate primer. Woods subject to tannin bleedthrough (cedar, redwood, etc.) should be primed entirely with 3077 or 5088. If stains show through the primer coat, these areas should be primed again before finishing.

REMOVAL OF CONTAMINANTS – All contaminants, such as grease, oil, dirt, etc., which would interfere with either the adhesion or aesthetic appeal of the finish should be removed.

SURFACE PREPARATION AND PRIMING

WOOD AND MASONITE – Repair construction defects and countersink all nails. Prime all new wood and bare areas with 300 Acrylic House Paint Primer with Microban®. Allow primer to dry thoroughly (at least 4 hours at 75°F). Fill nail holes and apply one or two finish coats of paint as necessary.

PREVIOUSLY PAINTED SURFACES – This product will adhere to surfaces previously painted with oil-based or acrylic paints. Clean surface thoroughly to remove any dirt and contamination. Rinse thoroughly. Dull glossy surfaces with light sanding. Spot prime any bare areas with appropriate primer. Apply one or two finish coats.

BRICK, MASONRY AND STUCCO – Remove all efflorescence. Remove all oils and curing compounds with acid etching or sandblasting. Chalked surfaces should be cleaned vigorously and rinsed with water. Prime all bare surfaces with 300 Acrylic House Paint Primer with Microban®.

CONCRETE BLOCK – Fill construction defects with spackling. After removing all loose surface particles, fill porous block with 1051 Premium Block Filler.

AGED ALUMINUM SIDING AND AGED GALVANIZED METAL – Remove grease and oil with an appropriate solvent. Well weathered surfaces should be primed with 1959 Water-Tuff® Red Oxide Primer or 1912 Water-Tuff® Gray Primer.

LIMITATIONS OF USE – While this product provides a mildew resistant coating, growth may still occur if the substrate is not properly prepared prior to painting and/or if the substrate is consistently exposed to conditions conducive to mold, mildew, and algae. Examples of these conditions include, but are not limited to, under eaves, behind shrubbery and trees, and in areas that are consistently damp with little to no direct sunlight.

PRECAUTIONS:

PROTECT FROM FREEZING!

Do not take internally.

Close container after each use.

KEEP OUT OF REACH OF CHILDREN!

LIMITED WARRANTY

DAVIS-FROST, INC. warrants this product will perform satisfactorily when applied over properly prepared surfaces in accordance with label directions; product failure due to deterioration of the underlying surface or failure of previous products is excluded. If the product fails to perform to your satisfaction, return any unused portion to the store with proof-of-purchase and you will receive, as your sole remedy under this warranty, your choice of additional product of equal value or a full refund. THIS WARRANTY EXCLUDES LABOR OR THE COST OF LABOR FOR THE APPLICATION OF ANY PRODUCT AND EXCLUDES ANY INCIDENTAL OR CONSEQUENTIAL DAMAGES. Some states do not allow the exclusion or limitation of incidental or consequential damages, so the above limitations or exclusions may not apply to you. This warranty gives you specific rights, and you may also have other rights which vary from state to state.

120514

DAVIS-FROST, INC.

3416 Candler's Mountain Road ▪ Lynchburg, VA 24502 ▪ Ph (434)846-5277 ▪ Fx (434)846-0635