

19 HOUSE PAINT PRIMER

Exterior Oil/Alkyd

| | |
|----------------------------|---|
| DESCRIPTION: | A superior exterior house paint primer consisting of a blend of linseed oils and alkyd resin designed to give excellent holdout on the most porous wood surfaces. It flows smoothly, applies easily and dries to a hard, durable film which provides optimum adhesion for subsequent topcoats. |
| USES: | Use on wood siding and trim, window sashes, shutters and doors. For exterior use only. May be used under oil/alkyd or latex paints. |
| VEHICLE TYPE: | Alkyd and Linseed Oils |
| SHEEN: | Gloss |
| SPREAD RATE: | 350-450 square feet per gallon |
| DRYING TIME @ 75°F: | To touch: 12 hours To recoat: 24 hours |
| THINNER: | Do not thin this product. |
| APPLICATION: | Stir thoroughly before using. Application may be by brush, roller, or spray. Both airless and conventional spray may be used. Always wear a respirator when spraying and protect yourself and your surroundings from spray mist. |
| LIMITATIONS: | Do not apply when temperature might drop below 50°F within 4 hours. Do not paint in late afternoon or when there is danger of rain or moisture condensing on wet film. Do not use in high temperature (above 160°F) service. If used as a primer under latex type topcoats, two topcoats are strongly recommended for best mildew protection. |
| COLORS: | White, but may be slightly tinted. |
| CLEAN UP: | Clean up with mineral spirits while primer is still wet. This product is difficult to remove when dry. |
| AVAILABILITY: | Gallon and quart containers |
| % SOLIDS BY VOLUME: | 62.0% ± 2% |
| % SOLIDS BY WEIGHT: | 79.0% ± 2% |
| V. O. C.: | 308 grams/liter or 2.57 lbs./gal. |

SURFACE PREPARATION - GENERAL PRACTICE

For proper adhesion, surface should be clean, dry, and non-greasy. Remove mildew, dirt, surface contamination, loose and scaling paint, efflorescence, loose surface particles, and water soluble stains before painting. Allow all recommended primers to thoroughly dry before applying one or two coats of finish paint.

In the recommendations below, certain steps must be taken to prepare surfaces for painting no matter what the substrate is. Therefore, it is to be understood that as situations warrant, the following steps must be taken to assure a quality painting job.

REMOVAL OF MILDEW -- Remove mildew with a commercially prepared solution or use: 5 oz. (2/3 cup) Trisodium Phosphate (TSP), 3 oz. (1/3 cup) detergent, 1 qt. household bleach and 3 qts. warm water which will make a little over one gallon.

SEALING KNOTS AND STAINS WHICH MAY BLEED THROUGH PAINT FILM -- Spot prime knots or stained areas with 3077 ProMax Alkyd Uniblox Universal Primer and let dry. Then prime entire surface with #19 primer. Woods subject to tannin bleedthrough (cedar, redwood, etc.) should be primed entirely with 3077. If stains show through the primer coat, these areas should be primed again before finishing.

REMOVAL OF CONTAMINANTS -- All contaminants, such as grease, oil, dirt, etc., which would interfere with either the adhesion or aesthetic appeal of the finish should be removed.

SURFACE PREPARATION AND PRIMING

WOOD -- Repair construction defects and countersink all nails. Prime all new wood and bare wood with this product. Fill nail holes before applying finish coat(s). For repainting wood surfaces, remove loose paint and sand smooth the remaining edges. Spot prime bare areas with this primer before applying finish coat(s).

WARNING! If you scrape, sand or remove old paint, you may release lead dust. **LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE.** Wear a NIOSH-approved respirator to control lead exposure. Carefully clean up with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hotline at 1-800-424-LEAD or log on to www.epa.gov/lead.

PRECAUTIONS: **WARNING! COMBUSTIBLE LIQUID AND VAPOR.** Keep away from heat and flame. Avoid prolonged contact with skin and breathing of vapor or spray mist.
USE ONLY WITH ADEQUATE VENTILATION.

CAUTION!

Do not take internally.
Close container after each use.

**CONTAINS PETROLEUM
DISTILLATE!**

**KEEP OUT OF REACH
OF CHILDREN!**

LIMITED WARRANTY

DAVIS-FROST, INC. warrants this product will perform satisfactorily when applied over properly prepared surfaces in accordance with label directions; product failure due to deterioration of the underlying surface or failure of previous products is excluded. If the product fails to perform to your satisfaction, return any unused portion to the store with proof-of-purchase and you will receive, as your sole remedy under this warranty, your choice of additional product of equal value or a full refund. THIS WARRANTY EXCLUDES LABOR OR THE COST OF LABOR FOR THE APPLICATION OF ANY PRODUCT AND EXCLUDES ANY INCIDENTAL OR CONSEQUENTIAL DAMAGES. Some states do not allow the exclusion or limitation of incidental or consequential damages, so the above limitations or exclusions may not apply to you. This warranty gives you specific rights, and you may also have other rights which vary from state to state.