

**200 SERIES ALKYD SEMI-GLOSS ENAMEL**

Interior

<b>DESCRIPTION:</b>	A rugged alkyd semi-gloss enamel for use on interior surfaces which produces a smooth, durable and scrubbable finish, free of brush and sag marks. Ideal for high traffic areas.
<b>USES:</b>	Use on properly prepared interior surfaces such as woodwork, cabinets, doors, trim, shelving and furniture. Also for use on properly prepared drywall, plaster, masonry, concrete block and metal.
<b>VEHICLE TYPE:</b>	Alkyd
<b>SHEEN:</b>	Semi-Gloss
<b>SPREAD RATE:</b>	350-450 square feet per gallon. Coverage figures do not include loss due to surface irregularities and porosity of material or loss due to application method or mixing.
<b>DRYING TIME @ 75°F:</b>	To touch: 4 hours      To recoat: 24 hours      To full cure: 7-14 days Drying times listed may vary depending on temperature, humidity, film build, color and air movement.
<b>THINNER:</b>	Do not thin this product.
<b>APPLICATION:</b>	Stir thoroughly before using. Application may be by brush, roller or spray. Most types of spray equipment are acceptable for spray application. Always wear a respirator when spraying and protect yourself and your surroundings from spray mist. Clean up with mineral spirits while paint is still wet.
<b>LIMITATIONS:</b>	Do not apply when temperature is below 50°F. Do not paint over damp or wet surfaces. Do not use in high temperature (160°F) service.
<b>COLOR:</b>	For custom tint colors, see "Color Is" Color System.
<b>AVAILABILITY:</b>	Gallon and Quart containers
<b>% SOLIDS BY VOLUME:</b>	60.0% ± 2% (bases vary)
<b>% SOLIDS BY WEIGHT:</b>	75.0% ± 2% (bases vary)
<b>V. O. C.:</b>	345 grams/liter or 2.88 lbs/gal (bases vary slightly)

*\*Product data calculations based on 200 White.*

SURFACE PREPARATION - GENERAL PRACTICE

For best adhesion, surfaces should be clean, dry, non-greasy and properly primed. Remove mildew, dirt, grease, loose rust, and loose scaling paint before painting. Sand glossy surfaces to a dull luster. Allow all recommended primers to dry thoroughly prior to painting.

In the recommendations below, certain steps must be taken to prepare surfaces for painting independent of the substrate. Therefore, the following steps must be taken to assure a quality paint job:

REMOVAL OF MILDEW -- Remove mildew with a commercially prepared solution or use: 5 oz. (2/3 cup) Trisodium Phosphate (TSP), 3 oz. (1/3 cup) detergent, 1 qt. household bleach and 3 qts. warm water which will make a little over one gallon.

SEALING KNOTS AND STAINS WHICH MAY BLEED THROUGH PAINT FILM – Spot prime knots or stained area with 3077 ProMax Alkyd Uniblox Universal Primer or 5088 ProMax “Eco-Green” Acrylic Uniblox Bonding Primer, let dry, then prime entire surface with appropriate primer. Woods subject to tannin bleedthrough (cedar, redwood, etc.) should be primed entirely with 3077 or 5088. If stains show through the primer coat, these areas should be primed again before finishing.

REMOVAL OF CONTAMINANTS – All contaminants, such as grease, oil, dirt, etc., which would interfere with either the adhesion or aesthetic appeal of the finish should be removed.

SURFACE PREPARATION AND PRIMING

NEW WOOD -- Repair construction defects and counter sink all nails. Prime with 3077 Alkyd Uniblox Universal Primer. Allow undercoat to dry thoroughly (at least 24 hours at 70°F). Sand lightly with fine grit sandpaper to remove raised grain. Fill nail holes, knots, corners, etc. with latex caulk or wood putty. Apply one or two finish coats of paint as necessary.

NEW DRYWALL -- Repair construction defects and fill openings with spackling. Prime with 5062 ProMax Latex Drywall Primer. Allow primer to dry thoroughly (at least 2 hours at 70°F). Scuff sand with fine sandpaper to remove raised nap. Apply one or two coats of finish paint as necessary.

PLASTER AND MASONRY -- Apply only to firm, fully cured and dust free plaster or masonry surfaces. Repair construction defects and fill openings with spackling. Prime with 5062 ProMax Latex Drywall Primer. Allow primer to dry thoroughly (at least 2 hours at 70°F). Inspect for "dry spots" in plaster and if necessary, spot prime these areas. Apply one or two finish coats of paint as necessary.

CONCRETE BLOCK -- Repair construction defects and fill openings with spackling. Prime with 1051 Premium Masonry Block Filler. Use a brush, roller or trowel to work the block filler well into the concrete blocks. Allow the block filler to dry thoroughly (at least 8 hours at 70°F). Apply one or two finish coats of paint as necessary. For best results, block filler should be lightly sanded prior to topcoating.

FERROUS METAL -- Remove all loose mill scale, rust, dirt and old coatings with abrasive cleaning. Prime with 59 Red Oxide metal primer. Allow primer to dry thoroughly (at least 24 hours at 75°F) before applying topcoat(s).

PREVIOUSLY PAINTED SURFACES -- Remove loose, flaking paint and sand glossy enamel surfaces to a dull sheen. Spot prime bare areas with the appropriate primer and allow to dry thoroughly. Apply one or two coats of finish paint as necessary.

**PRECAUTIONS:** CAUTION! COMBUSTIBLE! Keep away from heat and flame. Avoid prolonged contact with skin and breathing vapor or spray mist. Do not take internally. Close container after each use. USE ONLY WITH ADEQUATE VENTILATION. KEEP OUT OF REACH OF CHILDREN!

**LIMITED WARRANTY**

DAVIS-FROST, INC. warrants this product will perform satisfactorily when applied over properly prepared surfaces in accordance with label directions; product failure due to deterioration of the underlying surface or failure of previous products is excluded. If the product fails to perform to your satisfaction, return any unused portion to the store with proof-of-purchase and you will receive, as your sole remedy under this warranty, your choice of additional product of equal value or a full refund. THIS WARRANTY EXCLUDES LABOR OR THE COST OF LABOR FOR THE APPLICATION OF ANY PRODUCT AND EXCLUDES ANY INCIDENTAL OR CONSEQUENTIAL DAMAGES. Some states do not allow the exclusion or limitation of incidental or consequential damages, so the above limitations or exclusions may not apply to you. This warranty gives you specific rights, and you may also have other rights which vary from state to state.