

**3077 PROMAX UNIBLOX PRIMER/SEALER/STAIN BLOCKER**

Interior/Exterior Oil-Based

- DESCRIPTION:** A fast drying alkyd based primer, sealer, and stain blocker for use on most interior and exterior surfaces. This product uniformly seals porous surfaces and can be topcoated with any latex or oil/alkyd paint.
- USES:** For exterior application, can be used on wood, metal, masonry, and previously painted surfaces. Blocks out tannin stains on redwood, cedar and pine. May be used for whole house priming on siding and trim.
- For interior surfaces, can be used on drywall, carved plaster, woodwork and ceiling tiles. Blocks out discolorations caused by smoke, water, ink, crayon and grease stains. Use as an undercoat for enamel finishes.
- VEHICLE TYPE:** Alkyd
- SHEEN:** Low
- SPREAD RATE:** 350 to 450 square feet per gallon on smooth, nonporous surface
- DRYING TIME @ 75°F:** To touch: 30 mins. To recoat or topcoat: 2 hrs.  
Proper ventilation will aid drying time.
- THINNER:** Do not thin this product.
- APPLICATION:** Stir thoroughly before using. Application may be by brush, roller, or spray. Both airless and conventional spray may be used. Always wear a respirator when spraying and protect yourself and your surroundings from spray mist.
- LIMITATIONS:** Do not apply over damp areas. Do not apply when air or surface temperature is below 50°F. Do not apply over wallcovering.
- COLORS:** White. May be tinted with universal colorant up to 2 ounces per gallon when used as an undercoat.
- CLEAN UP:** Clean up with mineral spirits while product is still wet. 3077 is difficult to remove when dry.
- AVAILABILITY:** 5-gallon and gallon containers
- % SOLIDS BY VOLUME:** 52.0% ± 2%
- % SOLIDS BY WEIGHT:** 76.0% ± 2%
- V. O. C.:** Less than 400 grams/liter

---

---

SURFACE PREPARATION

For best adhesion surfaces should be clean, free of dirt, grease, wax, etc. 3077 has good adhesion to glossy surfaces but a light sanding will give the best adhesion. If washing is necessary use a non-sudsing detergent, like TSP, and rinse thoroughly and allow surface to dry before painting. Always allow the previous coat to thoroughly dry before repainting. **Note:** After priming stained areas, always test small section with application of topcoat before applying to entire project. If the stain comes through, apply a second coat of 3077 and retest.

TINTING: May be tinted with universal colorant up to two ounces per gallon when used as an undercoat. Do not tint for stain blocking application.

STAINS: Apply one coat of 3077 over water and rust stains, smoke and fire damage, crayon, lipstick and grease marks, ink, and graffiti. Some stains may require two coats.

WOOD: 3077 is perfect for use on wood either as an undercoat or to block out tannin stains on redwood. Apply one or two coats as needed. Also use over troublesome knots and sap streaks.

PLASTER AND DRYWALL: This product is an excellent primer and sealer for plaster and drywall. Apply only to firm, fully cured and dust free plaster and drywall. After priming drywall, may need to scuff with fine sandpaper to remove raised nap.

**WARNING!** If you scrape, sand or remove old paint, you may release lead dust. **LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE.** Wear a NIOSH-approved respirator to control lead exposure. Carefully clean up with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hotline at 1-800-424-LEAD or log on to [www.epa.gov/lead](http://www.epa.gov/lead).

**PRECAUTIONS! FLAMMABLE! Keep away from heat and flame.  
Use only with adequate ventilation.**

**CAUTION!**

Do not take internally.  
Close container after each use.

**CONTAINS PETROLEUM  
DISTILLATE!**

**KEEP OUT OF REACH  
OF CHILDREN!**

**LIMITED WARRANTY**

DAVIS-FROST, INC. warrants this product will perform satisfactorily when applied over properly prepared surfaces in accordance with label directions; product failure due to deterioration of the underlying surface or failure of previous products is excluded. If the product fails to perform to your satisfaction, return any unused portion to the store with proof-of-purchase and you will receive, as your sole remedy under this warranty, your choice of additional product of equal value or a full refund. THIS WARRANTY EXCLUDES LABOR OR THE COST OF LABOR FOR THE APPLICATION OF ANY PRODUCT AND EXCLUDES ANY INCIDENTAL OR CONSEQUENTIAL DAMAGES. Some states do not allow the exclusion or limitation of incidental or consequential damages, so the above limitations or exclusions may not apply to you. This warranty gives you specific rights, and you may also have other rights which vary from state to state.