

3900 SERIES CLASSIC PRO-MAX “ECO-GREEN” SATIN

Interior/Exterior Acrylic

- DESCRIPTION:** A professional, general purpose satin acrylic paint. This product is economical, applies easily, and dries to a durable satin finish.
- USES:** Use on properly prepared exterior surfaces of wood, brick, masonry, stucco, concrete block, aged aluminum siding, primed metal, aged galvanized metal and hard board such as Hardiplank or Masonite. This durable satin finish is excellent for exterior trim and doors as well as wood siding. Also for use on interior surfaces such as wood trim, walls and ceilings where a durable, satin finish is desired.
- VEHICLE TYPE:** Acrylic Blend
- SHEEN:** Satin: 18 – 22 @ 60°
- COVERAGE:** Approximately 350-450 square feet per gallon. Coverage figures do not include loss due to surface irregularities and porosity of material or loss due to application method or mixing.
- DRYING TIMES @ 75°F:** To touch: 1 hour To recoat: 4 hours To full cure: 14-30 days
Drying times listed may vary depending on temperature, humidity, film build, color and air movement.
- THINNER:** If necessary, thin sparingly with small amounts of water.
- APPLICATION:** Stir thoroughly. Application may be by brush, roller or spray. Always wear a respirator when spraying and protect yourself and your surroundings from spray mist. For best results and protection from the elements, we recommend one primer coat and two topcoats on all previously unpainted surfaces.
- LIMITATIONS:** Avoid use in direct sunlight on a hot day. Do not apply when temperature is below 50°F, this may affect color and sheen. Do not paint in late afternoon or where there is danger of rain or moisture condensing on the wet film. Do not use in high temperature (160°F) service.
- COLORS:** White and Tint Bases. For custom tint colors, see “Color Is” Color System.
- CLEAN UP:** Clean up with soap and warm water while paint is still wet. Dry paint is almost impossible to remove.
- AVAILABILITY:** White and White Base 5-gallon and gallon containers. Tint bases in gallons only.
- % SOLIDS BY VOLUME:** 37.0% ± 2% (bases vary)
- % SOLIDS BY WEIGHT:** 51.0% ± 2% (bases vary)
- V. O. C.:** 114 grams/liter (bases vary), 0.95 lbs/gal**Product data calculations based on 3901.*

100316

DAVIS-FROST, INC.

3416 Candler's Mountain Road ▪ Lynchburg, VA 24502 ▪ Ph (434)846-5277 ▪ Fx (434)846-0635

SURFACE PREPARATION - GENERAL PRACTICE

For proper adhesion, surface should be clean, dry, non-greasy and properly primed. Remove mildew, dirt, surface contamination, loose and scaling paint, efflorescence, loose surface particles, water soluble stains and rust before painting. Allow all recommended primers to thoroughly dry before applying one or two coats of finish paint.

In the recommendations below, certain steps must be taken to prepare surfaces for painting independent of the substrate. Therefore, the following steps must be taken to assure a quality paint job:

REMOVAL OF MILDEW -- Remove mildew with a commercially prepared solution or use: 5 oz. (2/3 cup) Trisodium Phosphate (TSP), 3 oz. (1/3 cup) detergent, 1 qt. household bleach and 3 qts. warm water which will make a little over one gallon.

SEALING KNOTS AND STAINS WHICH MAY BLEED THROUGH PAINT FILM -- Spot prime knots or stained areas with 3077 ProMax Alkyd Uniblox Universal Primer or 5088 Acrylic Uniblox Bonding Primer and let dry. Then prime entire surface with appropriate primer. Woods subject to tannin bleedthrough (cedar, redwood, etc.) should be primed entirely with 3077 or 5088. If stains show through the primer coat, these areas should be primed again before finishing.

REMOVAL OF CONTAMINANTS -- All contaminants, such as grease, oil, dirt, etc., which would interfere with either the adhesion or aesthetic appeal of the finish should be removed.

SURFACE PREPARATION AND PRIMING

PREVIOUSLY PAINTED SURFACES -- This product is self-priming and no primer is necessary on previously painted surfaces. Spot prime any bare areas with appropriate primer. Apply one or two finish coats.

WOOD AND MASONITE -- Repair construction defects and countersink all nails. Prime all new wood and bare areas with 300 Acrylic House Paint Primer or 5088 Acrylic Uniblox Bonding Primer. Allow primer to thoroughly dry (at least 4 hours at 75°F). Fill nail holes and apply one or two finish coats of paint as necessary.

BRICK, MASONRY AND STUCCO -- Remove all efflorescence. Remove all form oils and curing compounds with acid etching or sandblasting. Chalked surfaces should be cleaned vigorously and rinsed with water. Prime all bare surfaces with 300 Acrylic House Paint Primer or 5088 Acrylic Uniblox Bonding Primer.

CONCRETE BLOCK -- Fill construction defects with spackling. After removing all loose surface particles, fill porous block with 1051 Premium Block Filler.

AGED ALUMINUM SIDING AND AGED GALVANIZED METAL -- Remove grease and oil with an appropriate solvent. Well weathered surfaces should be primed with 1959 Water-Tuff® WB Red Oxide Primer or 1912 Water-Tuff® Gray DTM Primer.

WARNING! If you scrape, sand or remove old paint, you may release lead dust. **LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE.** Wear a NIOSH-approved respirator to control lead exposure. Carefully clean up with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hotline at 1-800-424-LEAD or log on to www.epa.gov/lead.

CAUTION!

Do not take internally.
Close container after each use.

PROTECT FROM FREEZING!

**KEEP OUT OF REACH
OF CHILDREN!**

LIMITED WARRANTY

DAVIS-FROST, INC. warrants this product will perform satisfactorily when applied over properly prepared surfaces in accordance with label directions; product failure due to deterioration of the underlying surface or failure of previous products is excluded. If the product fails to perform to your satisfaction, return any unused portion to the store with proof-of-purchase and you will receive, as your sole remedy under this warranty, your choice of additional product of equal value or a full refund. THIS WARRANTY EXCLUDES LABOR OR THE COST OF LABOR FOR THE APPLICATION OF ANY PRODUCT AND EXCLUDES ANY INCIDENTAL OR CONSEQUENTIAL DAMAGES. Some states do not allow the exclusion or limitation of incidental or consequential damages, so the above limitations or exclusions may not apply to you. This warranty gives you specific rights, and you may also have other rights which vary from state to state.