

5062 “ECO-GREEN” FLAT DRYWALL PRIMER

Interior Latex

DESCRIPTION:	An interior latex primer specifically formulated to provide excellent coverage, adhesion, and hold-out over drywall. Can be used as a primer under alkyd or latex finish coats and is ideal under flat, eggshell, or semi-gloss finishes. Provides excellent sealing properties, is easy to apply, dries quickly, and cleans up with water.
USES:	An interior primer sealer under all types of latex and alkyd paints. May be used on gypsum wallboard/drywall.
VEHICLE TYPE:	Acrylic Resins
GLOSS / SHEEN:	Flat / Low
SPREAD RATE:	350-450 square feet/gallon
DRYING TIME @ 75°F:	Usually dries to touch in about 30 minutes, longer at colder temperatures. May be recoated when completely dry – about 2 hours.
THINNER:	If necessary, add up to 1/2 pint of water per gallon.
APPLICATION:	Stir thoroughly before using. Application may be by brush, roller or spray. Most types of spray equipment are acceptable for spray application. Always wear a respirator when spraying and protect yourself and your surroundings from spray mist.
LIMITATIONS:	Do not apply when temperature is below 50°F. Do not use in high temperature (160°F) service. For interior use only.
COLOR:	White; may be lightly tinted
CLEAN UP:	Clean up with soap and warm water while primer is still wet. Dry primer is difficult to remove.
AVAILABILITY:	5-gallon and gallon containers
% SOLIDS BY VOLUME:	26.0% ± 2%
% SOLIDS BY WEIGHT:	45.0% ± 2%
V. O. C.:	49 grams/liter or .42 lbs/gal

SURFACE PREPARATION - GENERAL PRACTICE

For best adhesion, surfaces should be clean, dry, and non-greasy. Remove all mildew, dirt and grease before priming. Allow this primer to thoroughly dry before applying one or two coats of finish paint.

NEW DRYWALL: Fill construction defects with spackling. Prime with this product. Allow to thoroughly dry. Scuff sand with fine sandpaper to remove raised nap before applying finish coat(s).

WARNING! If you scrape, sand or remove old paint, you may release lead dust. **LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE.** Wear a NIOSH-approved respirator to control lead exposure. Carefully clean up with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hotline at 1-800-424-LEAD or log on to www.epa.gov/lead.

CAUTION!

Do not take internally.
Close container after each use.

PROTECT FROM FREEZING!

**KEEP OUT OF REACH
OF CHILDREN!**

LIMITED WARRANTY

DAVIS-FROST, INC. warrants this product will perform satisfactorily when applied over properly prepared surfaces in accordance with label directions; product failure due to deterioration of the underlying surface or failure of previous products is excluded. If the product fails to perform to your satisfaction, return any unused portion to the store with proof-of-purchase and you will receive, as your sole remedy under this warranty, your choice of additional product of equal value or a full refund. THIS WARRANTY EXCLUDES LABOR OR THE COST OF LABOR FOR THE APPLICATION OF ANY PRODUCT AND EXCLUDES ANY INCIDENTAL OR CONSEQUENTIAL DAMAGES. Some states do not allow the exclusion or limitation of incidental or consequential damages, so the above limitations or exclusions may not apply to you. This warranty gives you specific rights, and you may also have other rights which vary from state to state.