

### 5088 PROMAX “ECO-GREEN” BONDING PRIMER SEALER/STAIN BLOCKER

Interior/Exterior 100% Acrylic

- DESCRIPTION:** A fast drying 100% acrylic primer, sealer, and stain blocker for use on most interior and exterior surfaces. This product uniformly seals porous surfaces and can be topcoated with any latex or oil/alkyd paint.
- USES:** For exterior application, can be used on wood, aged galvanized metal, masonry, and previously painted surfaces. May be used for whole house priming on siding and trim. For interior surfaces, can be used on drywall, carved plaster, woodwork, and ceiling tiles. Adheres to glossy surfaces. Blocks out tannin stains on redwood, cedar and pine. Blocks out discolorations caused by smoke, water, ink, crayon and grease.
- VEHICLE TYPE:** Acrylic
- SHEEN:** Low
- SPREAD RATE:** 300 to 450 square feet per gallon on smooth, nonporous surface
- DRYING TIME @ 75°F:** To touch: 30 minutes      To recoat: 2 hours. Maximum stain blocking occurs when allowing the product to dry for 4 hours prior to topcoating or recoating. Proper ventilation will aid drying time.
- THINNER:** If necessary, thin sparingly with water. Do not thin for stain blocking applications.
- TINTING:** May be tinted with universal colorant up to 2 ounces per gallon when used as an undercoat. Do not tint for stain blocking applications.
- APPLICATION:** Stir thoroughly before using. Application may be by brush, roller, or spray. Both airless and conventional spray may be used. Always wear a respirator when spraying and protect yourself and your surroundings from spray mist.  
**Precaution:** After area has been primed, test for “bleed through” by applying topcoat to a small section. If such “bleedthrough” occurs, apply a second coat of 5088 before topcoating entire area and retest.
- LIMITATIONS:** Do not apply over continually damp areas. Do not apply if surface or air temperature is below 50° F. Longer than normal drying times can be caused by low temperature, high humidity, or poor ventilation.
- COLORS:** White – For stain blocking applications use of colorants is not recommended.
- CLEAN UP:** Clean up with soap and warm water while primer is still wet. Dry primer is difficult to remove.
- AVAILABILITY:** 5-gallon and gallon containers
- % SOLIDS BY VOLUME:** 35.0% ± 2%
- % SOLIDS BY WEIGHT:** 47.0% ± 2%
- V. O. C.:** Less than 50 grams/liter

020618

**DAVIS-FROST, INC.**

3416 Candler's Mountain Road ▪ Lynchburg, VA 24502 ▪ Ph (434)846-5277 ▪ Fx (434)846-0635

SURFACE PREPARATION

For best adhesion surfaces should be clean, dry and non-greasy. Remove all dirt, mildew and grease before priming. Allow previous coat to thoroughly dry prior to painting.

Remove all contaminants such as grease, oil, dirt, etc. If washing is necessary, use a non-sudsing detergent like TSP, rinse thoroughly, and allow to dry before repainting. Normal good painting practices should be followed.

GLOSSY SURFACES: Will adhere to glossy surfaces without sanding, such as oil gloss enamels, Masonite, even glass. However, light sanding to a dull luster will provide the best adhesion. Scrape resistance develops in 3 to 4 days as primer cures.

STAINS: Apply one coat of 5088 over water and rust stains, smoke and fire damage, water, crayon, lipstick and grease marks, ink, and graffiti. Some stains may require two coats. Blocks out tannin stains on redwood, cedar and pine.

WOOD: 5088 is perfect for use on wood either as an undercoat or to block out tannin stains on redwood. Apply one or two coats as needed. Also use over troublesome knots and sap streaks.

PLASTER & DRYWALL: This product is an excellent primer and sealer for plaster and drywall. Apply only to firm, fully cured and dust-free plaster and drywall. After priming drywall, may need to scuff with fine sandpaper to remove raised nap.

AGED GALVANIZED METAL: Surface should be exterior weathered for six months and be clean, dry and free from dirt, grease, mildew and other surface contaminants. Rusty galvanized metals should be cleaned and primed with 1912 Water-Tuff® Gray DTM Primer or 1959 Water-Tuff® WB Red Oxide Primer.

**WARNING!** If you scrape, sand or remove old paint, you may release lead dust. **LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE.** Wear a NIOSH-approved respirator to control lead exposure. Carefully clean up with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hotline at 1-800-424-LEAD or log on to [www.epa.gov/lead](http://www.epa.gov/lead).

**CAUTION!**

Do not take internally.  
Close container after each use.

**PROTECT FROM FREEZING!**

**KEEP OUT OF REACH  
OF CHILDREN!**

**LIMITED WARRANTY**

DAVIS-FROST, INC. warrants this product will perform satisfactorily when applied over properly prepared surfaces in accordance with label directions; product failure due to deterioration of the underlying surface or failure of previous products is excluded. If the product fails to perform to your satisfaction, return any unused portion to the store with proof-of-purchase and you will receive, as your sole remedy under this warranty, your choice of additional product of equal value or a full refund. THIS WARRANTY EXCLUDES LABOR OR THE COST OF LABOR FOR THE APPLICATION OF ANY PRODUCT AND EXCLUDES ANY INCIDENTAL OR CONSEQUENTIAL DAMAGES. Some states do not allow the exclusion or limitation of incidental or consequential damages, so the above limitations or exclusions may not apply to you. This warranty gives you specific rights, and you may also have other rights which vary from state to state.