

68 NU-BRITE ALUMINUM

Alkyd Leafing Aluminum

DESCRIPTION:	A heavy-duty alkyd leafing aluminum formulated for interior and exterior use on properly primed metal, including metal roofs. Dries to a high gloss.
USES:	Excellent for use on machinery, metal work, and roofs. Ideal for industrial maintenance where durability is critical.
VEHICLE TYPE:	Soya Alkyd
SHEEN:	Gloss
SPREAD RATE:	350-450 square feet per gallon on smooth, primed or sealed surfaces.
DRYING TIME @ 75°F:	To touch: 4 hours To recoat: 24 hours
THINNER:	Do not thin this product.
APPLICATION:	Stir thoroughly before using. Application may be by brush, roller, or spray. Both airless and conventional spray may be used. Always wear a respirator when spraying and protect yourself and your surroundings from spray mist.
LIMITATIONS:	Do not apply on galvanized or aluminum substrates. Do not apply when temperatures might drop below 50°F. Do not paint in late afternoon or when there is danger of rain or moisture condensing on the wet film. Always wear a respirator when spraying and protect yourself and your surroundings from spray mist.
COLORS:	Bright Aluminum
CLEAN UP:	Clean up with mineral spirits while paint is still wet. Dry paint is almost impossible to remove.
AVAILABILITY:	5-gallon, gallon and quart containers
% SOLIDS BY VOLUME:	39.0 ± 2%
% SOLIDS BY WEIGHT:	50.0% ± 2%
V. O. C.:	This product contains less than 500 grams/liter.

SURFACE PREPARATION – GENERAL PRACTICE

For best adhesion, surfaces should be clean, dry, non-greasy and properly primed. Remove dirt, grease, rust, and loose scaling paint before painting. Sand glossy surfaces to a dull luster. Allow previous coats to thoroughly dry prior to painting.

In the recommendations below, certain steps must be taken to prepare surfaces for painting independent of the substrate. Therefore, the following steps must be taken to assure a quality paint job:

REMOVAL OF CHALK AND DIRT FROM EXISTING PAINTED SURFACES – Remove by washing vigorously with a non-sudsing detergent which leaves no surface residue.

REMOVAL OF MILDEW – Remove mildew with a commercially prepared solution or use: 5 oz. (2/3 cup) Trisodium Phosphate (TSP), 3 oz. (1/3 cup) detergent, 1 qt. household bleach and 3 qts. warm water which will make a little over one gallon.

SURFACE PREPARATION AND PRIMING

NEW TIN ROOFS – Remove grease and oil with a solvent. If the surface is very slick, it should be sanded to remove gloss. Prime with 59 Red Oxide Metal Primer or other acceptable metal primer. Allow primer to dry before applying topcoat(s).

FERROUS METAL – Remove all loose rust, mill scale, dirt and old paint (sanding edges smooth). Prime with 59 Red Oxide Metal Primer (spot prime for repaints).

NOTES – During the early spring and fall periods of the year, daytime temperatures may seem warm. However, nighttime temperatures may be much colder than expected which will cause dry time of paint to be lengthened significantly. This leaves the film open to moisture attack for longer periods. Frequently during these times of the year, condensation will form on freshly painted surfaces in the form of dew. This will cause patchy areas where the dew will etch the paint surface. When viewed, this appears as a splotchy color change on the painted surface.

WARNING! If you scrape, sand or remove old paint, you may release lead dust. **LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE.** Wear a NIOSH-approved respirator to control lead exposure. Carefully clean up with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hotline at 1-800-424-LEAD or log on to www.epa.gov/lead.

PRECAUTIONS! COMBUSTIBLE! Keep away from heat and flame.
Avoid prolonged contact with skin and breathing of vapor or spray mist.
USE ONLY WITH ADEQUATE VENTILATION.

CAUTION!

Do not take internally.
Close container after each use.

**CONTAINS PETROLEUM
DISTILLATE!**

**KEEP OUT OF REACH
OF CHILDREN!**

LIMITED WARRANTY

DAVIS-FROST, INC. warrants this product will perform satisfactorily when applied over properly prepared surfaces in accordance with label directions; product failure due to deterioration of the underlying surface or failure of previous products is excluded. If the product fails to perform to your satisfaction, return any unused portion to the store with proof-of-purchase and you will receive, as your sole remedy under this warranty, your choice of additional product of equal value or a full refund. THIS WARRANTY EXCLUDES LABOR OR THE COST OF LABOR FOR THE APPLICATION OF ANY PRODUCT AND EXCLUDES ANY INCIDENTAL OR CONSEQUENTIAL DAMAGES. Some states do not allow the exclusion or limitation of incidental or consequential damages, so the above limitations or exclusions may not apply to you. This warranty gives you specific rights, and you may also have other rights which vary from state to state.