

---

---

**EWC 3000 ELASTOMERIC WALL COATING**

100% Acrylic

<b>DESCRIPTION:</b>	A heavy duty, high build, elastomeric acrylic emulsion coating that provides a waterproof finish on cementitious surfaces. Its unique formulation provides maximum protection from wind driven rain. Its permeable film bridges hairline cracks and allows moisture vapor from within the structure to escape. It is an above-grade coating that provides outstanding durability, flexibility, and weatherability with excellent dirt and mildew resistance.
<b>USES:</b>	Provides outstanding protection to all properly prepared cementitious surfaces, including concrete block, brick, masonry, split face block, stucco, poured concrete and incidental wood and metal.
<b>VEHICLE TYPE:</b>	100% Acrylic Latex
<b>SHEEN:</b>	Low-Lustre
<b>SPREAD RATE:</b>	125-150 square feet per gallon
<b>DRY TIMES:</b>	To touch: 4-6 hrs.                      To recoat: after overnight dry
<b>THINNER:</b>	If necessary add up to 1 quart of clean water per 5 gallons of product for first coat. Subsequent coats should be applied at full strength.
<b>APPLICATION:</b>	Stir thoroughly before using. Application may be by brush, roller, or airless sprayer. For best results, apply first coat by brush or roller for proper penetration and surface coverage. Second coat may be sprayed or rolled.
<b>LIMITATIONS:</b>	For exterior use only. Do not apply at temperatures below 45°F, or when temperature is forecasted to be below 45°F before product is fully cured (3 to 5 days). Do not apply in temperatures above 100°F. Avoid painting in late afternoon or when dew is likely to form, or when there is danger of rain or moisture condensing on the wet film.
<b>RECOMMENDED DRY FILM:</b>	4-5 mils
<b>COLOR:</b>	White; tintable to white and medium base colors
<b>CLEAN UP:</b>	Clean up with soap and warm water while coating is still wet. This coating is almost impossible to remove when dry.
<b>AVAILABILITY:</b>	5-gallon containers
<b>% SOLIDS BY VOLUME:</b>	45% ± 2%

# Product Data (pg. 2)

## EWC 3000



**% SOLIDS BY WEIGHT:** 62% ± 2%

**V.O.C.:** 89 grams/liter or .74 lbs./gal.

**CLEAN UP:** Warm soapy water

**SURFACE PREPARATION:** All surfaces must be clean, dry, and free of dirt, mildew, chalk, and other surface contaminants. For best results, surface should be cleaned by power washing.

**TYPICAL PROPERTIES:**

Elongation:	200% (ASTM D23%)
Tensile Strength:	275 PSI (ASTM D23%)
Permeance:	Perms 35-40 (ASTM D1653)
Wind Driven Rain Test:	PASSES (ASTM D6904-03)

**WARNING!** If you scrape, sand or remove old paint, you may release lead dust. **LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE.** Wear a NIOSH-approved respirator to control lead exposure. Carefully clean up with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hotline at 1-800-424-LEAD or log on to [www.epa.gov/lead](http://www.epa.gov/lead).

### **CAUTION!**

Do not take internally.

Close container after each use.

**PROTECT FROM FREEZING!**

**KEEP OUT OF REACH  
OF CHILDREN!**

### **LIMITED WARRANTY**

DAVIS-FROST, INC. warrants this product will perform satisfactorily when applied over properly prepared surfaces in accordance with label directions; product failure due to deterioration of the underlying surface or failure of previous products is excluded. If the product fails to perform to your satisfaction, return any unused portion to the store with proof-of-purchase and you will receive, as your sole remedy under this warranty, your choice of additional product of equal value or a full refund. THIS WARRANTY EXCLUDES LABOR OR THE COST OF LABOR FOR THE APPLICATION OF ANY PRODUCT AND EXCLUDES ANY INCIDENTAL OR CONSEQUENTIAL DAMAGES. Some states do not allow the exclusion or limitation of incidental or consequential damages, so the above limitations or exclusions may not apply to you. This warranty gives you specific rights, and you may also have other rights which vary from state to state.

081616

**DAVIS-FROST, INC.**

3416 Candler's Mountain Road ▪ Lynchburg, VA 24502 ▪ Ph (434)846-5277 ▪ Fx (434)846-0635