
LX-00101 YELLOW SURE FOOT ENAMEL

Description:	A tough, rugged, abrasion resistant alkyd floor coating for interior and exterior use on concrete, wood and metal surfaces.	
Uses:	Excellent for use on floors, steps, and ramps in heavy traffic areas and for industrial maintenance where durability and washability are important.	
Vehicle Type:	Alkyd	
% Solids by Volume:	57.0% ± 2%	
% Solids by Weight:	79.0% ± 2%	
Viscosity @ 77°F:	105 – 115 KU	
Weight per Gallon:	13.43 Lbs/Gal	
V.O.C.:	2.81 Lbs/Gal	
Recommended Film Thickness:	3 - 4 mils DFT	Coverage: 250 - 300 sq ft.
Theoretical Coverage:	900 Sq Ft/Gal @ 1 mil	
Gloss:	Flat	
Drying Time @77°F:	To touch: 1 ½ hrs.	
Solvent:	Aliphatic Hydrocarbons	
Thinning:	Not recommended but if necessary use mineral spirits.	
Flash Point:	106°F	
Clean Up:	Clean up with mineral spirits while paint is still wet. This product is difficult to remove when dry.	
Application:	Brush or roll recommended.	
Compliant to:	OTC (Ozone Transport Commission) requirements FDA (Incidental food contact) requirements Rule 66	

Continues on back....

Limitations: Apply only in good weather. Do not apply unless air, surface, and material temperature are at least 50° (10°C). Do not apply unless surface temperature is at least 5°F (3°C) above the dew point or when it is likely that moisture will contact surface of wet film. Do not use in immersion or high temperature service.

Surface Preparation: Clean surface carefully. Remove dirt, grease, rust, old paint and other foreign materials by wire brushing, chipping or scraping. Wash surface with detergent solution, rinse thoroughly with clear water & allow to dry. New or dense concrete surfaces must be etched to insure proper bonding. After cleaning, rinse with a solution of zinc sulphate (2 ½ lbs. per gallon of water) or muriatic acid (3%). Allow to dry without rinsing.

Mixing: Paint should be mixed as necessary to insure homogeneity.

Shelf Life: Once opened 6 months in containers. In general, unopened paint will have a shelf life exceeding one year.

Safety: This product and recommended thinners contain solvents and/or other chemical ingredients. Please observe proper health and safety procedures during storage, handling, application and drying periods. For optimum safety, user is directed to consult the current Safety Data Sheet for this product and other products being used coincidentally. When using in a confined area, consult the current OSHA or ANSI bulletins on safety requirements.

WARNING! If you scrape, sand or remove old paint, you may release lead dust. **LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE.** Wear a NIOSH-approved respirator to control lead exposure. Carefully clean up with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hotline at 1-800-424-LEAD or log on to www.epa.gov/lead.

PRECAUTIONS! COMBUSTIBLE! Keep away from heat and flame.
Avoid prolonged contact with skin and breathing of vapor or spray mist.
USE ONLY WITH ADEQUATE VENTILATION.

CAUTION!

Do not take internally.
Close container after each use.

**CONTAINS PETROLEUM
DISTILLATE!**

**KEEP OUT OF REACH
OF CHILDREN!**

LIMITED WARRANTY

DAVIS-FROST, INC. warrants this product will perform satisfactorily when applied over properly prepared surfaces in accordance with label directions; product failure due to deterioration of the underlying surface or failure of previous products is excluded. If the product fails to perform to your satisfaction, return any unused portion to the store with proof-of-purchase and you will receive, as your sole remedy under this warranty, your choice of additional product of equal value or a full refund. THIS WARRANTY EXCLUDES LABOR OR THE COST OF LABOR FOR THE APPLICATION OF ANY PRODUCT AND EXCLUDES ANY INCIDENTAL OR CONSEQUENTIAL DAMAGES. Some states do not allow the exclusion or limitation of incidental or consequential damages, so the above limitations or exclusions may not apply to you. This warranty gives you specific rights, and you may also have other rights which vary from state to state.